

# iQ Eminent

## Datasheet

|                                                                    | Norm                                                           | iQ Eminent 2.0 mm (2022 renewal)                          | iQ Eminent Tiles 2.0 mm (2022 renewal)                    |
|--------------------------------------------------------------------|----------------------------------------------------------------|-----------------------------------------------------------|-----------------------------------------------------------|
| Classification                                                     |                                                                |                                                           |                                                           |
| Product type                                                       | ISO 10581                                                      | Homogeneous vinyl floor covering                          |                                                           |
| Binder content                                                     | ISO 10581                                                      | Type I                                                    |                                                           |
| Commercial classification                                          | ISO 10874                                                      | 34 Very Heavy                                             |                                                           |
| Industrial classification                                          | ISO 10874                                                      | 43 Heavy                                                  |                                                           |
| Technical Characteristics                                          |                                                                |                                                           |                                                           |
| Surface treatment                                                  |                                                                | New iQ PUR                                                |                                                           |
| Surface Restoration                                                |                                                                | Yes                                                       |                                                           |
| Total thickness                                                    | ISO 24346                                                      | 2 mm                                                      |                                                           |
| Wear layer thickness                                               | ISO 24340                                                      | 2 mm                                                      |                                                           |
| Total weight                                                       | ISO 23997                                                      | 2750 g/m²                                                 |                                                           |
| Performance for CE Marking                                         |                                                                |                                                           |                                                           |
| Declaration of Performance #                                       | EN 14041                                                       | 0019-0008-DoP-2013-07                                     |                                                           |
| Reaction to fire                                                   | EN 13501-1                                                     | Bfl-s1                                                    |                                                           |
| Reaction to fire                                                   | EN ISO 9239-1                                                  | ≥ 8 kW/m²                                                 |                                                           |
| Reaction to fire - EN ISO 11925-2                                  | EN ISO 11925-2                                                 | Pass                                                      |                                                           |
| Static Electrical Propensity                                       | EN 1815                                                        | Antistatic (≤ 2 kV)                                       |                                                           |
| Thermal resistance                                                 | EN 12667                                                       | ~0,010 m²•K/W                                             |                                                           |
| Slip resistance (EN 13893)                                         | EN 13893                                                       | Class DS (μ ≥ 0,30)                                       |                                                           |
| Technical Performance                                              |                                                                |                                                           |                                                           |
| Residual indentation                                               | EN ISO 24343-1                                                 | Best measured value: 0,02 mm<br>≤ 0,10 mm                 |                                                           |
| Slip resistance                                                    | EN 16165 Annex B (formerly DIN 51130)                          | R9/R10 - On demand                                        |                                                           |
| Slip Resistance (EN 16165 Annex C)                                 | EN 16165 Annex C (formerly BS 7976-2; Pendulum Test Slider 96) | Low risk of slip                                          |                                                           |
| Curl resultant to heat                                             | EN ISO 23999                                                   | ≤ 8 mm for rolls                                          | ≤ 2 mm for tiles                                          |
| Clean room                                                         | ISO 14644-1                                                    | ISO class 4                                               |                                                           |
| Riboflavin Test                                                    | Fraunhofer method                                              | Class 0 : Excellent                                       |                                                           |
| Castor chair                                                       | ISO 4918                                                       | Suitable                                                  |                                                           |
| Light fastness                                                     | ISO 105-B02                                                    | ≥ 7                                                       |                                                           |
| Dimensional stability                                              | EN ISO 23999                                                   | Average Measured Value : ≤ 0.40 % for rolls               | Average measured value : ≤ 0.25 % for tiles               |
| Ease of Decontamination                                            | ISO 8690 – DIN 25415                                           | Excellent                                                 |                                                           |
| Chemical resistance                                                | ISO 26987                                                      | Excellent Resistance                                      |                                                           |
| Bacteria Resistance                                                | ISO 846 Part C                                                 | Does not promote growth                                   |                                                           |
| Underfloor heating                                                 |                                                                | Suitable (subfloor temperature maximum 27°C)              |                                                           |
| Wetroom approval                                                   | EN 13553 Annex A                                               | Watertight                                                |                                                           |
| Seam Strength Average Value                                        | EN 684                                                         | ≥ 400 N/50mm                                              |                                                           |
| Sustainability performances                                        |                                                                |                                                           |                                                           |
| Recyclability through ReStart®                                     |                                                                | Offcuts / Post-use - Contact Tarkett for more information |                                                           |
| Recycled content                                                   |                                                                | 25,5 %                                                    |                                                           |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)               |                                                                | 3,48 kg CO₂eq /m²                                         |                                                           |
| Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario) |                                                                | 1,81 kg CO₂eq /m²                                         |                                                           |
| Total VOC Emissions (after 28 days)                                | EN 16516                                                       | Platinum (≤ 10 µg/m³)                                     |                                                           |
| Dimensions and designs                                             |                                                                |                                                           |                                                           |
| Roll                                                               |                                                                | Roll 2 x 23 m                                             |                                                           |
| Tile                                                               |                                                                |                                                           | Tile 610 x 610 mm - 14 tiles=5,2 m²/box - 40 boxes/pallet |
| Number of designs available                                        |                                                                | 26                                                        | 26                                                        |



iQ  
NEW FOR LIFE™



The above information is subject to modification for the benefit of further improvement (04/05/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

