

# Aquarelle Wall HFS

## Datasheet

| Classification                                       | Norm                      | Tarkett Value                                                 |
|------------------------------------------------------|---------------------------|---------------------------------------------------------------|
| Product type                                         | EN 233                    | Vinyl wallcovering in roll form                               |
| Technical Characteristics                            | Norm                      | Tarkett Value                                                 |
| Total thickness                                      | EN ISO 24346              | 0,92 mm                                                       |
| Total weight                                         | EN ISO 23997              | 1500 g/m²                                                     |
| Wear layer thickness                                 | EN ISO 24340              | 0,12 mm                                                       |
| Installation method                                  |                           | Glue-Down                                                     |
| Performance for CE Marking                           | Norm                      | Tarkett Value                                                 |
| Declaration of Performance #                         | EN 15102                  | 0131-0032-DoP-2020-01                                         |
| Reaction to fire                                     | EN 13501-1                | B-s2,d0 glued on any non-metal A1 or A2-s1,d0 class substrate |
| Technical Performance                                | Norm                      | Tarkett Value                                                 |
| Light fastness                                       | EN ISO 1056802            | ≥ 6                                                           |
| Bacteria Resistance                                  | ISO 846 Part C            | Does not promote growth                                       |
| Chemical resistance                                  | EN ISO 26987              | Good resistance                                               |
| Spongeability, washability, lyability, brushability  | EN 12956                  | Super washable and brushable                                  |
| Riboflavin Test                                      | ISO 4628-1 - VDI 2083 P17 | Class 0 : Excellent                                           |
| Seam Strength Average Value                          | ISO 16906                 | ≥ 150 N/50mm                                                  |
| Sustainability performances                          | Norm                      | Tarkett Value                                                 |
| Recyclability through ReStart®                       |                           | Offcuts - Contact Tarkett for more information                |
| Recycled content                                     |                           | 4,5 %                                                         |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3) |                           | 4,44 kg CO <sub>2</sub> eq /m²                                |
| Total VOC Emissions (after 28 days)                  | ISO 16000-9               | Platinum (≤ 10 µg/m³)                                         |
| Formaldehyde emission                                |                           | E1                                                            |
| Dimensions and designs                               |                           |                                                               |
| Roll                                                 |                           | Roll 0,49 x 35m<br>Roll 2 x 35 m                              |
| Number of designs available                          |                           | 33                                                            |



The above information is subject to modification for the benefit of further improvement (02/06/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.