

Technical Datasheet

Spray adhesive Tarkospray - Professional

ADHESIVES & WELDING

DESCRIPTION

Water-based acrylic adhesive delivered in an aerosol can for professionals (Installers, Contractors, Building owners, Specifiers).

Key features:

- High grade acrylic adhesive, ready to use.
- 70% faster to apply, no tools required.
- After floor covering laying, can be used immediatly.
- Safe solution: non toxic, non flammable, same propellant as asthma pumps, zero CFC.
- Environmental properties: 80% less glue doing the same job, low VOC emissions, improved recycling process.

Compatible flooring:

- Heterogeneous and homogeneous floorings.

Main segments of application:



TECHNICAL INFORMATION

Product

Unit weight (g) 625 (15m²)

Packaging

Pieces per box	6
Box size (cm)	24 x 17 x 33
Box weight (kg)	5.0
Pallet size (m)	1.0 x 1.12 x 0.86
Pallet weight (kg)	440
Min. order	20 boxes

ARTICLE CODE

Languages	SAP Code	EAN Code
English, French, German, Dutch, Polish	1460 001	1094922378780
English, Swedish, Spanish, Italian, Portuguese	1460 005	1094922319899

INSTALLATION

- The subfloor must be level, flat, clean, free from marks, dry, solid, smooth and not exposed to moisture.
- The building, subfloor, flooring and adhesive must be acclimatized to a minimum 15°C.
- Store adhesive at 15°C minimum temperature for 24 hours prior to installation.
- Ensure subfloor, flooring and surrounding areas are clean and dust free. Damp-mop the subfloor if dust is present (you can check with a white cloth).
- Shake the aerosol can well and remove the cap.
- Hold the can horizontal approximately 50-76 cm above the substrate and spray adhesive smoothly walking right to left, respecting density of flakes.
- Allow adhesive to dry until there is no transfer when touched lightly.
- Lay down your flooring into the adhesive
- Complete bond by applying pressure.

CLEANING & MAINTENANCE

Adhesive stains can be removed with damp sponge when still fresh or with white gas later on.