# iD inspiration Click Solid 55

## Datasheet

| Classification | Norm | Tarkett Value |
|---|---|---|
| Product type | EN ISO 10582 | Heterogeneous poly(vinyl chloride) floor coverings |
| Domestic classification | EN ISO 10874 | 23 Heavy |
| Commercial classification | EN ISO 10874 | 33 Heavy |
| Industrial classification | EN ISO 10874 | 42 General |
| Commercial warranty (in years) | | 10 years |
| Residential warranty (in years) | | 20 years |
| **Technical Characteristics** | **Norm** | **Tarkett Value** |
| Total thickness | EN ISO 24346 | 5 mm |
| Wear layer thickness | EN ISO 24340 | 0,55 mm |
| Total weight | EN ISO 23997 | 8850 g/m² |
| Binder content | EN ISO 10582 | Type I |
| Surface treatment | | TEKTANIUM ® |
| Embossing in Register | | Yes |
| Bevelled edges | | No bevel<br>4 sides |
| Installation method | | Click |
| **Performance for CE Marking** | **Norm** | **Tarkett Value** |
| Declaration of Performance # | EN 14041 | 0197-0011-DoP-2021-02 |
| **Technical Performance** | **Norm** | **Tarkett Value** |
| Dimensional stability | EN ISO 23999 | Average measured value : ≤ 0.10 % |
| Curl resultant to heat | EN ISO 23999 | ≤ \|1\| mm |
| Reaction to fire | EN 13501-1 | Bfl-s1 |
| Residual indentation | EN ISO 24343-1 | ≤ 0,10 mm |
| Furniture leg | EN ISO 16581 | No damage |
| Furniture leg | EN ISO 16581 | No damage |
| Castor chair | EN ISO 4918 | No damage |
| Impact sound reduction - ΔLw | EN ISO 717-2 | 5 dB |
| Reduction of in-room impact noise | NF S31-074 | Class C (≤ 85 dB) |
| Thermal resistance | EN ISO 10456 | 0,05 m²•K/W |
| Light fastness | EN ISO 105-B02 | ≥ 6 |
| Chemical resistance | EN ISO 26987 | Good resistance |
| Slip resistance | DIN 51130 | R9<br>R10 |
| Slip resistance (EN 13893) | EN 13893 | Class DS (μ ≥ 0,30) |
| Peeling Resistance | EN ISO 24345 | ≥ 50N/50mm |
| Underfloor heating | | Suitable (subfloor temperature maximum 27°C) |
| **Sustainability performances** | **Norm** | **Tarkett Value** |
| Recyclability through ReStart® | | Offcuts / Post-use - Contact Tarkett for more information |
| Recycled content | ISO 14021 | 35 % |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3) | | 13,38 kg $CO_2$eq /m² |
| Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario) | | 6,79 kg $CO_2$eq /m² |
| Total VOC Emissions (after 28 days) | EN 16516 | Platinum (≤ 10 µg/m³) |

| Dimensions and designs | |
|---|---|
| Plank | Plank 1211 x 190,5mm - 7 planks=1,61 m²/box - 56 boxes/pallet<br>Plank 240 x 1491 mm - 5 planks=1,79 m²/box - 51 boxes/pallet |
| Tile | Tile 323,8 x 601 mm - 9 tiles=1,75 m²/box - 54 boxes/pallet<br>Tile 490 x 991 mm - 3 tiles=1,46 m²/box - 62 boxes/pallet |
| Number of designs available | 42 |

Embossing in register : on Authentics references

Slip resistance DIN : R9/R10 depending on embossing

The above information is subject to modification for the benefit of further improvement (07/04/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website https://www.tarkett.com. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.