

iD Square Loose-Lay

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 11638	Heterogeneous poly(vinyl chloride) floor coverings
Commercial classification	EN ISO 10874	34 Very Heavy
Industrial classification	EN ISO 10874	42 General
Commercial warranty (in years)		10 years
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	4,50 mm
Wear layer thickness	EN ISO 24340	0,80 mm
Total weight	EN ISO 23997	5195 g/m²
Binder content	EN ISO 10582	Type I
Surface treatment		TEKTANIUM ®
Installation method		Loose-Lay
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0120-067-DoP-2024-03
Technical Performance	Norm	Tarkett Value
Dimensional stability	EN ISO 23999	≤ 0,10 %
Reaction to fire	EN 13501-1	Bfl-s1 loose-lay on an A1fl and/or A2fl substrate Cfl-s1 loose-lay on a wooden sub-floor
Residual indentation	EN ISO 24343-1	Average measured value: 0,13 mm
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Impact sound reduction - ΔLw	EN ISO 717-2	17 dB
Reduction of in-room impact noise	NF S31-074	Class A (≤ 65 dB)
Thermal resistance	EN ISO 10456	0,05 m²·K/W
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Excellent Resistance
Slip resistance	DIN 51130	R10
Slip resistance (EN 13893)	EN 13893	Class DS (μ ≥ 0,30)
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Offcuts / Post-use - Contact Tarkett for more information
Recycled content	ISO 14021	20,2 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		9,62 kg CO₂eq /m²
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		7,52 kg CO₂eq /m²
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m³)
Dimensions and designs		
Plank	Plank 646,6 x 129,3mm - 25 planks=2,08 m²/box - 25 boxes/pallet Plank 1000 x 250 mm - 12 planks=3 m²/box - 44 boxes/pallet Plank 1200x200mm - 12 planks=2,88 m²/box - 44 boxes/pallet	
Tile	Tile 50 x 50 cm - 12 tiles=3 m²/box - 44 boxes/pallet Tile 100 x 100 cm - 1 Tile=1 m²/box - 1 box/pallet	
Number of designs available	41	



The above information is subject to modification for the benefit of further improvement (07/04/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

