PE Silver 2 mm: 15 x 1 m (15m²)

Art. nr - 68815

Scan this QR code to view this product on our website.



Description

PE Silver is a PE foam laminated with a reinforced aluminum moisture barrier. PE Silver offers high compressive strength and creates a completely flat and smooth surface. It is suitable for laminate and parquet flooring for residential use.

- Excellent acoustic improvement
- Stable and easy to install
- Integrated vapor/moisture barrier with 50 mm flap and tape
- Compatible with underfloor heating

PE Silver 2 mm: 15 x 1 m (15m²)

Art. nr - 68815

Specifications

Floor type	Parquet / Laminate
Thickness	2 mm
Type of base floor	Fixed sand cement floor / Floating screed
Domestic use	Yes
PC (Punctual Conformability)	> 0.5 mm
CS	CS0
CS/CC (compressive Strength / Compressive Creep)	> 10 kPa
Product weight	40 g/m²
Product dimensions (Length)	15 m
Product dimensions (Width)	1 m
Product dimensions in m2	15 m²
Sound-reducing - ΔLw	19 dB ΔLw
TOG rating	0.67 TOG
Thermal resistance - R-value	0.067 m² K/W
DIBT certificate	Z-158.10-79
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
SD (Steam Diffusion)	20 micron
Density	20 kg/m³

PE Silver 2 mm: 15 x 1 m (15m²)

Art. nr - 68815

Material	Top layer: Non-woven polyethylene flat foam / Bottom layer: Metalized polypropylene 20 micron vapor/moisture barrier
Brand	Estillon
VOC label	A+
Laying method	Floating
Wheelchair load (Test method: EN 985)	Suitable
CS/CC (Compressive Strength / Compressive Creep)	> 10 kPa

PE Silver 2 mm: 15 x 1 m (15m²)

Art. nr - 68815







