Universol Akustik 3 mm: 5 x 1 m (5 m²)

Art. nr - 68139

Scan this QR code to view this product on our website.



Description

Universol 3.0 mm is a very heavy acoustic underlay based on a PU/mineral blend, with a weight of approximately 660 kg/m³. Thanks to its low thermal resistance, this underlay is highly suitable for use in combination with underfloor heating. Universol 3.0 mm is suitable for the floating installation of laminate and parquet in both residential application areas (NK21-23) and commercial application areas (NK31-32).

- Highly suitable for underfloor heating
- Very high reduction of impact sound and walking sound
- High compressive strength
- Vapour permeable, without integrated moisture protection

Installation instructions:

- Allow the underlay to acclimatise for at least 24 hours in its original packaging in the room where it will be installed.

Universol Akustik 3 mm: 5 x 1 m (5 m²)

Art. nr - 68139

- The optimum humidity level is between 50–70%, and the room temperature should be between 15–20 °C.
- The strips of underlay must always be laid perpendicular to the lengthwise direction of the floor covering.
- The subfloor must be completely level, dry, dust-free and free of cracks, in accordance with DIN 18365/18202.
- We recommend using trapezoid blades to cut the underlay.
- Allow an edge gap of at least approx. 5–10 mm, depending on the floor covering and its thickness.
- Always follow the installation instructions provided by the manufacturer of the floor covering as well.
- The use of acoustic underlays may affect the floor's indentation behaviour. When using office chairs, we therefore always recommend a suitable office chair mat.

Important:

This acoustic underlay has been tested in accordance with CEN/TS-13654 by EMPLF/MMFA and meets the increased requirements for floating installation of laminate and parquet.

In general, the use of acoustic underlays may affect the floor's indentation behaviour, including its suitability for castor chairs. We therefore always recommend the use of a suitable office chair mat.

If the installation instructions are not followed, Estillon cannot be held liable. If in doubt, please contact Estillon.

If the installation instructions and other guidelines are not followed, Estillon cannot be held liable for damage or claims resulting from incorrect installation. If in doubt, please contact the supplier.

Universol Akustik 3 mm: 5 x 1 m (5 m²)

Art. nr - 68139

Specifications

Floor type	Laminate / Parquet
Thickness	3 mm
PC (Punctual Conformability)	2,3 mm
CS/CC (compressive Strength / Compressive Creep)	100 kPa
Product weight	1959 gr/m²
Product dimensions (Length)	5 m
Product dimensions (Width)	1 m
Product dimensions in m2	5 m²
Sound-reducing - ΔLw	19 dB ΔLw
TOG rating	0,10 TOG
Thermal resistance - R-value	0,010 m² K/W
DIBT certificate	Z-158-10-220
Fire classification	Bfl-s1
Density	660 kg/m³
Material	PU/mineral blend + PET
Laying method	Floating
Installation instruction explanation	Perpendicular to the laying direction of the top floor. Prevent the joints of the underlay and the top floor from aligning.
Wheelchair load (Test method: EN 985)	Suitable

Universol Akustik 3 mm: 5 x 1 m (5 m²)

Art. nr - 68139













